

## United States Patent and Trademark Office

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER OF PATENTS AND TRADEMARKS Washington, D.C. 20231 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/769,339	01/26/2001	Yoshihisa Takubo	Q62555	5113
75	90 09/23/2002			
SUGHRUE, MION, ZINN, MACPEAK & SEAS, PLLC Suite 800 2100 Pennsylvania Avenue, N.W.			EXAMINER	
			MAKI, STEVEN D	
Washington, DC 20037-3213			ART UNIT	PAPER NUMBER
			1733	/
			DATE MAILED: 09/23/2002	6

Please find below and/or attached an Office communication concerning this application or proceeding.

		<b>∠</b> .D		
	Applicati n N .	Applicant(s)		
<b>→</b>	09/769,339	TAKUBO, YOSHIHISA		
Office Action Summary	Examiner	Art Unit		
·	Steven D. Maki	1733		
The MAILING DATE of this communication ap	pears on the c ver sheet with	the correspondence address		
Period for Reply  A SHORTENED STATUTORY PERIOD FOR REPL THE MAILING DATE OF THIS COMMUNICATION.  - Extensions of time may be available under the provisions of 37 CFR 1.  after SIX (6) MONTHS from the mailing date of this communication.  - If the period for reply specified above is less than thirty (30) days, a repless of the period for reply is specified above, the maximum statutory period.  - Failure to reply within the set or extended period for reply will, by statut.  - Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).  Status	136(a). In no event, however, may a repoly within the statutory minimum of thirty (will apply and will expire SIX (6) MONTH e. cause the application to become ABA	ly be timely filed 30) days will be considered timely. 1S from the mailing date of this communication. NDONED (35 U.S.C. § 133).		
1) Responsive to communication(s) filed on				
	 his action is non-final.			
Since this application is in condition for allow closed in accordance with the practice under Disposition of Claims	vance except for formal matte	ers, prosecution as to the ments is 11, 453 O.G. 213.		
4)⊠ Claim(s) <u>1-20</u> is/are pending in the applicatio	n.			
4a) Of the above claim(s) is/are withdra	awn from consideration.			
5) Claim(s) is/are allowed.				
6)⊠ Claim(s) <u>1-20</u> is/are rejected.				
7) Claim(s) is/are objected to.				
8) Claim(s) are subject to restriction and/o	or election requirement.			
Application Papers				
9) The specification is objected to by the Examine				
10) The drawing(s) filed on is/are: a) acce				
Applicant may not request that any objection to the				
11) The proposed drawing correction filed on	_ , , , , ,	approved by the Examiner.		
If approved, corrected drawings are required in re				
12) The oath or declaration is objected to by the Ex	xammer.			
Priority under 35 U.S.C. §§ 119 and 120	a and and to consider OF LLO O. S.	440(a) (d) an (0		
13)⊠ Acknowledgment is made of a claim for foreig	in priority under 35 U.S.C. §	1 19(a)-(d) or (i).		
a)⊠ All b)□ Some * c)□ None of:	As barra basa sasairad			
Certified copies of the priority documents have been received.      Certified copies of the priority documents have been received in Application No				
_ , , ,	•	<del>-</del>		
<ul><li>3. Copies of the certified copies of the price application from the International Both See the attached detailed Office action for a list</li></ul>	ureau (PCT Rule 17.2(a)).			
14) Acknowledgment is made of a claim for domest	tic priority under 35 U.S.C. §	119(e) (to a provisional application).		
a) ☐ The translation of the foreign language pr 15)☐ Acknowledgment is made of a claim for domes				
Attachment(s)				
1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948) 3) Information Disclosure Statement(s) (PTO-1449) Paper No(s)	5) Notice of Inf	ormal Patent Application (PTO-152)		
S. Patent and Trademark Office	·-			

<sup>--</sup> Art Unit: 1733

1) Applicant is advised that should claim 2 are be found allowable, claim 13 will be objected to under 37 CFR 1.75 as being a substantial duplicate thereof. When two claims in an application are duplicates or else are so close in content that they both cover the same thing, despite a slight difference in wording, it is proper after allowing one claim to object to the other as being a substantial duplicate of the allowed claim. See MPEP § 706.03(k).

Claims 2 and 13 have the same scope.

- 2) The following is a quotation of the second paragraph of 35 U.S.C. 112:

  The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.
- 3) Claims 2, 7, 10, 11 and 13 are rejected under 35 U.S.C. 112, second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which applicant regards as the invention.

The difference in scope between claims 2 and 13 is unclear.

In claim 7, what is "tread halt width"? Should "tread halt width" be --tread half width--?

In claim 10, the scope and meaning of "self-closing type groove" is unclear.

When is the groove self closing? Is the self closing type groove a sipe which thereby excludes a circular groove 42 as shown in figure 3A?

4) The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless -

<sup>(</sup>b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

Art Unit: 1733

(e) the invention was described in-

- (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effect under this subsection of a national application published under section 122(b) only if the international application designating the United States was published under Article 21(2)(a) of such treaty in the English language; or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that a patent shall not be deemed filed in the United States for the purposes of this subsection based on the filing of an international application filed under the treaty defined in section 351(a).
- 5) The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
  - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 6) Claims 1-2, 4-8, 12-13 and 15-16 are rejected under 35 U.S.C. 102(e) as being anticipated by Kobayashi (US 6347653).

Applicant cannot rely upon the foreign priority papers to overcome this rejection because a translation of said papers has not been made of record in accordance with 37 CFR 1.55. See MPEP § 201.15.

7) Claims 1-4, 6-7, 9, 12-15 and 17-19 are rejected under 35 U.S.C. 102(b) as anticipated by or, in the alternative, under 35 U.S.C. 103(a) as obvious over Japan 204 (JP 5-155204).

Japan '204 discloses a pneumatic tire having a tread comprising wide lug grooves 4, a narrow circumferential recess 6 on the central plane of the tire and sequentially formed narrow recesses 7. The sequential narrow recesses are located just outside a position spaced by W/3 from the center plane of the tire. The negative ratio of the tread is 50-80%. See abstract and figures. The lug groove 4 has a depth of

Art Unit: 1733

15 mm. Each of the narrow circumferential recess 6 and the narrow recesses 7 have a width of 3-15% of the tread width and a depth of 7.5 mm. The depth of each recess is 50% of the lug groove depth (7.5 mm / 15 mm = 50%). Japan '204 teaches that the narrow recesses are more shallow than the lug grooves. See machine translation. The negative ratio of the narrow circumferential recess and the sequential narrow recesses other than the wide lug grooves therefore must define a negative ratio of 6-30%, which corresponds to the claimed range of 10-25%; it being noted that the midpoint of the range 6-30% is 18% which falls within the claimed range of 10-25%.

The tire of claims 1-4, 6-7, 9, 12-15 and 17-19 is anticipated by the tire of Japan '204. In any event: As to claim 1, it would have been obvious to one of ordinary skill in the art to use a negative ratio of the center region other than the lug groove of 10-25% for the tread of Japan '204 since (a) the negative ratio of Japan '204's tread other than the lug groove is defined by the narrow recesses, (b) the circumferential narrow recess contributes only 3-15% to the negative ratio and the sequential narrow and (c) the sequential narrow recesses contribute only 3-15% to the negative ratio. Hence, Japan '204 teaches a negative ratio other than the lug groove of 3-30% and this range of 6-30% is suggestive of the claimed range of 10-25%. As to claim 12 (depth), the claimed recess depth being 10-45% of lug groove depth would have been obvious in view of Japan '204's teaching to use a recess depth which is more shallow than the lug groove depth; a recess depth which is 50% of the lug groove depth being provided as an example. As to claim 17, the "recess portion continuously" reads on the circumferential groove 6 and the "another recess portion" reads on the narrow grooves

Art Unit: 1733

7. As to the remaining claims: The "auxiliary groove segment" reads on the narrow groove 7. The claimed lug groove bottom configuration is suggested by the lug groove bottom illustrated in figure 3.

8) Claims 1-20 are rejected under 35 U.S.C. 103(a) as being unpatentable over the admitted prior art (page 19 lines 2-3) in view of Japan '913 (JP 5-96913) and/or Great Britain '587 (GB 691587) and optionally further in view of Europe '288 (EP 593288) and/or Japan '113 (JP 11-139113).

The admitted prior art teaches a pneumatic tire having a tread comprising lug grooves having a maximum depth of 60 mm or more but no recesses. The admitted prior art teaches that this tire is used for construction (heavy) vehicles. The admitted prior art teaches that heat generation is increased due to a higher speed of the heavy vehicle. The admitted prior art does not teach using recess(es) in the admitted prior art tread having lug grooves to reduce heat generation. However, it would have been obvious to one of ordinary skill in the art to provide the claimed recess(es) in the center region of the tread having lug grooves for a heavy duty tire of the admitted prior art such that the negative ratio of the center region other than the lug groove is 10-25% to reduce heat generation in the admitted prior art tire since (a) Japan '913 suggests forming recesses (holes) in land portions of a tread for a heavy duty pneumatic tire to reduce heat generation and/or Great Britain '587's teaching to form a narrow center circumferential recess and sequential narrow grooves (slits) in a tread having lug grooves for a heavy duty pneumatic tire which is to have reduce heat generation and optionally (b) it is well known per se in the tread art to use a center circumferential

**Art Unit: 1733** 

groove to reduce heat as evidenced by Europe '288. The limitation of the depth of the recess(es) being 10-45% of the lug groove depth would have been obvious in view of the depth of the recess(es) suggested by the secondary art – Great Britain '587 for example teaching a recesses depth of 1/3-2/3 of lug groove depth. The limitation of the configuration of the lug groove bottom would have been obvious in view of (a) the configuration of the lug groove bottom shown by Great Britain '587 and optionally (b) the lug groove configuration shown by Japan '113 – Japan '113 clearly teaching a groove depth gradually increasing toward the center plane of a tread having lug groves for a heavy duty tire.

## Remarks

- 9) The remaining references are cited of interest.
- 10) No claim is allowed.
- 11) Any inquiry concerning this communication or earlier communications from the examiner should be directed to Steven D. Maki whose telephone number is 703-308-2068. The examiner can normally be reached on Mon. Fri. 7:30 AM 4:00 PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Michael Ball can be reached on (703) 308-2058. The fax phone numbers for the organization where this application or proceeding is assigned are (703) 872-9310 for regular communications and (703) 872-9311 for After Final communications.

Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the receptionist whose telephone number is (703) 308-0661.

Steven D. Maki September 20, 2002 STEVEN D. MAKI FRIMARY EXAMINER

AU 1737